



Specifications

Battery	One AA battery, lasts 360 hours
Weight	108 g (3.8 oz)
Size	127 x 62 x 28mm (5 x 2.4 x 1.1in)
Measurement Units	Flow rate (mL/h), drops per minute (dp/m) and total volume (mL)
Alarm	80 dB at 10cm approx. Sounds at ±13% rate change or when flow stops
Minimum Chamber Diameter	13 mm (0.51in)
Maximum Chamber Diameter	21.1 mm (0.83in)
Compatible Drip Sets	10, 15, 20, 60 gtt/mL
Accuracy	± 1% drip rate
Warranty	1 year limited warranty

Standards Compliance

•	
Radiated Emissions	CISPR 11:2010
Ingress Protection	IP22
Electromagnetic compatibility	IEC 61000-4
Regulatory	US FDA 510(k) K150687, CE Mark,
	ISO 13485:2003 and ISO 13485:2003 CMDCAS

Additional Warnings for Customers in the USA

The following warnings apply only for customers intending to use the DripAssist device within the United States of America:

- Only trained, qualified personnel should operate the DripAssist.
- The DripAssist is not intended for home use.
- Caution: Federal law restricts this device to sale by or on the order of a licensed practitioner.



www.shiftlabs.com info@shiftlabs.com +1 206.369.1216 Corporate Headquarters 1600 Dexter Ave N • Suite A Seattle, WA 98109 United States Mailing Address 1752 NW Market St. #211 Seattle, WA 98107 United States